

HOLSAG CANADA

Seating Manufacturer

Specifications: Alex Barstool

Description

The attractive design of the Alex chair and matching barstool makes this line a popular choice for dining and hotel rooms. The high back on the chair has four slats that curve upwards, providing excellent back support. The padded, upholstered seat is very comfortable. A choice of many different fabrics is offered or customer supplied fabric can be used.

Dimensions: 24" (61 cm) Barstool

Height	38"	96.5 cm
Depth	21"	53 cm
Seat Width	18.5"	47 cm
Seat Depth	16.5"	42 cm
Seat Height	24"	61 cm
Stool Weight	15 lbs	6.8 kg
Carton Weight		
with 1 stool	25 lbs	11.4 kg
Carton Size		
19.25" x 20.25" x 45"		
48.5 cm x 51 cm x 113.4 cm		
Volume	10.2 cubic feet	

Note: The barstool is available in custom seat heights ranging from 24" (61 cm) to 30" (76 cm).

Dimensions: 30" (76 cm) Barstool

Height	43.5"	110 cm
Depth	21"	53 cm
Seat Width	18.5"	47 cm
Seat Depth	16.5"	42 cm
Seat Height	30"	76 cm
Stool Weight	17 lbs	7.7 kg
Carton Weight		
with 1 stool	27 lbs	12.3 cm
Carton Size		
19.25" x 20.25" x 45"		
48.9 cm x 51 cm x 113.4 cm		
Volume	10.2 cubic feet	

Fabric for upholstered seats

COM (Customer's Own Material) fabric required (chair and barstool):
.35 yd (.33 m)

Note: This is the estimated amount based on 54" (137 cm) wide material. The actual amount required may vary depending on special pattern matching and the width of the material.

Stock fabric: Black vinyl is available as a stock fabric.

Cushion Foam: High density 1.5" (3.8 cm) thick on seat

Standard kickplates are brass. Chrome kickplates are available upon request at the same price.

Wood

Species: 100% Solid European Beech Hardwood

Standard kickplates are brass. Chrome kickplates are available at the same price.

Construction

Joints: Mortise and tenon. Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root woodscrews.

Stain Colors

A wide range of standard stain colors is available as well as custom color matching. (A surcharge will apply to custom colors.)

9-Step Finishing Process

1. The bare wood of the assembled chair is thoroughly sanded using 120 grit paper.
2. One coat of stain is sprayed onto the entire chair.

3. The stain is handwiped to ensure an even color and maximum penetration into the wood.
4. The chair is inspected and any necessary adjustments made.
5. One coat of a catalyzed sealer is sprayed onto all wood parts to completely seal the wood.
6. Once dry, the sealer is sanded using 320 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.



Note: Specifications are subject to change without notice.

Holsag Canada

164 Needham Street
Lindsay, Ontario Canada
K9V 5R7
(705) 878-1970
(888) 745-0721 (U.S. & Canada)
Fax: (705) 878-1864

www.holsag.com