

# HOLSAG CANADA

Seating Manufacturer

## Specifications: Bulldog Benches

### Dimensions: 42" (106 cm) Bench

Height	35"	89 cm
Depth	17"	43 cm
Frame Width	42"	107cm
Seat Depth	16"	40 cm
Seat Height	18"	46 cm
Arms Height	28"	71 cm
Arms Outside	48"	122 cm
Weight	40 lbs	18 kg
Weight (with arms)	42 lbs	19 kg
Carton Size		
	21.25" x 49.25" x 36"	
	53.5 cm x 124 cm x 91 cm	

### Dimensions: 60" (151 cm) Bench

Height	35"	89 cm
Depth	17"	43 cm
Frame Width	60"	151 cm
Seat Depth	16"	40 cm
Seat Height	18"	46 cm
Arms Height	28"	71 cm
Arms Outside	66"	168 cm
Weight	60 lbs	27 kg
Weight (with arms)	62 lbs	28 kg
Carton Size		
	21.25" x 64.5" x 36"	
	53.5 cm x 162.5 cm x 91 cm	

### Wood

*Species:* 100% Solid European Beech Hardwood

### Construction

*Joints:* Mortise and tenon.  
Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root woodscrews.

### Stain Colors

A wide range of standard stain colors is available as well as custom color matching. (A surcharge will apply to custom colors.)

### 9-Step Finishing Process

1. The bare wood of the assembled bench is thoroughly sanded using 120 grit paper.
2. One coat of stain is sprayed onto the entire bench – including the underside of the seat.
3. The stain is handwiped to ensure an even color and maximum penetration into the wood.
4. The bench is inspected and any necessary adjustments made.
5. One coat of catalyzed sealer is sprayed onto all wood parts to completely seal the wood – including the underside of the seat.
6. Once dry, the sealer is sanded using 320 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.

*Note:* Specifications are subject to change without notice.

## Holsag Canada

164 Needham Street  
Lindsay, Ontario Canada  
K9V 5R7

(705) 878-1970

(888) 745-0721 (U.S. & Canada)

Fax: (705) 878-1864

[www.holsag.com](http://www.holsag.com)