

HOLSAG CANADA

Seating Manufacturer

Specifications: Courthouse Chair and Barstool

Description

The Courthouse seating line which includes a chair, armchair and barstool conveys a message of sophistication and quality. The solid European beech hardwood construction and durable catalyzed lacquer finish combine to create a beautiful, lasting seating line.

Dimensions: Chair

Height	32.75"	83 cm
Depth	21.5"	55 cm
Seat Width	18.25"	46.5 cm
Seat Depth	15.5"	39 cm
Seat Height	18"	46 cm
Chair Weight	17 lbs	6.4 kg
Carton Weight		
with 1 chair	27 lbs	12.3 kg
with 2 chairs	44 lbs	20 kg
Carton Size for 1 Chair		
18.25" x 22.25" x 37.5"		
46 cm x 56 cm x 95 cm		
Carton Volume for 1 Chair		
8.8 cubic feet		
Carton Size for 2 Chairs		
18.25" x 24.5" x 37.5"		
46 cm x 62 cm x 95 cm		
Carton Volume for 2 Chairs		
9.7 cubic feet		
<i>Note: Packing of the chairs is based on the shipping method.</i>		

The Courthouse chair is non-stacking.

Dimensions: Barstool

Height	46"	117 cm
Depth	21.5"	55 cm
Seat Width	18.25"	46.5 cm
Seat Depth	15.5"	39 cm
Seat Height	30"	76 cm
Stool Weight	21 lbs	9.5 kg
Carton Weight		
with 1 stool	31 lbs	14 kg
Carton Size for 1 Barstool		
19.25" x 20.25" x 45"		
48.9 cm x 51 cm x 113.4 cm		
Volume	10.2 cubic feet	

Note: The barstool is available in custom seat heights ranging from 24" (61 cm) to 30" (76 cm).

Wood

Species: 100% Solid European Beech Hardwood

Standard barstool kickplates are brass. Chrome kickplates are available at the same price.

Construction

Solid construction using a double layer of wood to reinforce the seat. Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root woodscrews.

Stain Colors

A wide range of standard stain colors is available as well as custom color matching. (A surcharge will apply to custom colors.)

9-Step Finishing Process

1. The bare wood of the assembled chair is thoroughly sanded using 120 grit paper.
2. One coat of stain is sprayed onto the entire chair – including the underside of the seat.
3. The stain is handwiped to ensure an even color and maximum penetration into the wood.
4. The chair is inspected and any necessary adjustments made.
5. One coat of a catalyzed sealer is sprayed onto all wood parts to completely seal the wood – including the underside of the seat.
6. Once dry, the sealer is sanded using 320 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.

8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.



Note: Specifications are subject to change without notice.

Holsag Canada

164 Needham Street
Lindsay, Ontario Canada
K9V 5R7
(705) 878-1970
(888) 745-0721 (U.S. & Canada)
Fax: (705) 878-1864

www.holsag.com