

ARCHITECTURAL SPECIFICATIONS

PANASONIC ADVANCED VENTILATION SERIES



LOW PROFILE VENTILATION FANS

FV-05VF2 WhisperFit

Ventilating fan shall be of the ceiling mount, ENERGY STAR rated type, with no less than 50 CFM and no more than 0.4 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge when used with the 4" duct. Power consumption shall be no greater than 15 watts and ENERGY STAR rated with efficiency rating of no less than 3.3 CFM/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. 3" duct adapter available with performance specifications as listed in the specification chart. Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring.

FV-08VF2 WhisperFit

Ventilating fan shall be of the ceiling mount, ENERGY STAR rated type, with no less than 80 CFM and no more than 0.8 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge when used with the 4" duct. Power consumption shall be no greater than 24.5 watts and ENERGY STAR rated with efficiency rating of no less than 3.3 CFM/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. 3" duct adapter available with performance specifications as listed in the specification chart. Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring.

FV-11VF2 WhisperFit

Ventilating fan shall be of the ceiling mount, ENERGY STAR rated type, with no less than 110 CFM and no more than 1.5 sones as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge when used with the 4" duct. Power consumption shall be no greater than 33.5 watts and ENERGY STAR rated with efficiency rating of no less than 3.3 CFM/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. 3" duct adapter available with performance specifications as listed in the specification chart. Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring.