

DIRECT FIRED

PROPANE / NATURAL GAS

Model	DF400	DF1000	DF1500
Capacity	400,000 BTU	1,000,000 BTU	1,500,000 BTU/HI FIRE 800,000 BTU/LOW/FIRE
Fuel	Vapor Propane/ Natural Gas	Vapor Propane/ Natural Gas	Vapor Propane/ Natural Gas
Manifold Pressure	Propane 1.1" w.c. Natural Gas 2.8" w.c.	Propane 2.4" w.c. Natural Gas 6.0" w.c.	Propane 3.2" w.c. Natural Gas 7.8" w.c.
Gas Consumption	157 CFH/ LP 4.35 US Gal/ HR 390 CFH/ NG 10.7 US Gal/ HR	393 CFH/ 10.9 US Gal/ HR/ LP 974 CFH/ 27.2 US Gal/ HR/ NG	589 CFH/ 16.5 US Gal/ HR/ LP 1461 CFH/ 40.8 US Gal/ HR/ NG
Gas Consumption	3/4" NPT	1.25" NPT	1.25" NPT
Electrical Requirements	120 Volts 15 Amps Circuit	120 Volts 20 Amp Circuit	120 Volts 20 Amp Circuit
Fan	2500 CFM 1/2 HP, 16" Diameter	7700 CFM 1 HP, 24" Diameter	7700 CFM 1 HP, 24" Diameter
Shipping Dimensions			
Gated (LxWxH)	51" x 30.5" x 33"	74.5" x 39.5" x 52.5"	74.25" x 39.5" x 52.5"
Weight	206 lbs	415 lbs	415 lbs
Approved	ETL	ETL	ETL