

# LED Undercabinet Light

## Installation instructions for models 021-0001 and 021-0002

**WARNING:** These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with the owners manual, current electrical codes and/or the current National Electric Code (NEC).

### **CAUTION - To reduce risk of fire, electric shock or injury to persons:**

1. This light is intended for indoor use only.
2. Not intended for lighting aquariums.
3. Mount light only to surfaces that are mechanically sound.
4. Do not link more than 40 watts total in a series.
5. Use only with 24V DC Plug-in Power Supply (021-0004). Factory warranty will be void if used with a non-recommended power supply, transformer or driver.
6. Not intended for recessed application.
7. To reduce the risk of heat build up, mount only with mounting clips included.

### **MOUNTING**

1. Locate desired position for light. Remember to leave 1" clearance at one or both ends to plug in power supply cord and/or linking extensions.
2. Mark location of mounting clips. These should be found already attached to the fixture, placed about a quarter of the way in from each end.
3. Remove mounting clips and hold one at a time at each marked location. Now, mark the location of mounting holes.
4. Use suitable fasteners to mount clips to mounting surface.
5. Snap LED light into clips.

### **ATTACHING POWER SUPPLY**

**NOTE:** This LED Under Cabinet Light is designed for use with a switched outlet above upper (kitchen) cabinets or below work surface for task lighting applications.

1. Plug power jack from plug-in power supply (021-0004) into LED Under Cabinet Light.
2. Run power jack cord (with its power supply) up to top of cabinets either between cabinet boxes or behind cabinets being careful not to pinch wires or damage wires in any way. Place power supply on top of cabinets.
3. Plug 120V cord into other side of power supply.
4. Plug power supply cord into 120V outlet.

### **LINKING UNITS**

1. A 24" linking extension is supplied with each fixture.
  2. Do not link more than 40 watts in a series.
- NOTE:** 021-0001 = 5 watts each, 021-0002 = 10 watts each



AMERICAN LIGHTING  
BRIGHT IDEAS • INNOVATIVE PRODUCTS

[www.americanlighting.com](http://www.americanlighting.com)

