

BN-TIER™

CORDLESS REBAR TYING TOOL



One TIER. Two Handles.

Our patented design allows you to easily change the handle from the vertical work position (above) to the horizontal work position (right) in just a few moments.

AUTOMATIC BENEFITS

- Reduces tying time, great for repetitious tying work.
- Reduces the risk of carpal tunnel and back injuries.
- One hand operation, allows other hand to hold rebar.
- Securely ties up to #10 (32mm) x #10 (32mm) rebars.
- Strong double tie wrap of 18 gauge galvanized wire.
- Consistent ties, no wire waste, only 1.6 seconds a tie.



Benner-Nawman, Inc.

3450 Sabin Brown Road
Wickenburg, AZ 85390
800-992-3833 or 928-684-2813
Fax: 928-684-7041



BNrebartools.com

Model Number	<i>BN-TIER</i> #BNT-64
Maximum Rebar Tying Capacity	#10 (32mm) x #10 (32mm) with the #64 wire guide installed
Tool Weight	8.4 lbs (3.8 kg) w/ battery & wire spool /
Shipping Weight	w/ standard equipment 27 lbs (12.25 kg)
Tool Dimensions	7.02" x 3.12" x 25.74" for horizontal work (180 x 80 x 660)
H x W x L (mm)	11.31" x 3.12" x 22.62" for vertical work (290 x 80 x 580)
Number of Parts	Only 75
Tying Speed	1.6 seconds per tie
Tie Wraps/Wire Size	(2) tie wraps of 18 gauge or 1.0 mm
Wire Spool Length/ Wire Types	(148 ft) 45 m per spool / Galvanized Wire only
Ties Per Coil	120 to 200
Wire Carton/ Shipping Weight	40 wire spools per carton / 29 lbs. (13 kg) per carton
Ties Per Battery Charge	750 ties per battery charge (4-5 wire spools)
Torque Adjustment	0-9 (increases wire tie tightness)
Standard Wire Guide Installed	#32 wire guide ties maximum #6 x #6 rebars
Optional Wire Guides	#26 wire guide ties maximum #3 x #4 rebars
Using the right size wire guide increases wire usage, tying speed & decreases clearance.	#51 wire guide ties maximum #8 x #8 rebars
	#64 wire guide ties maximum #10 x #10 rebars
Battery Type (#BN-12VCad)	Rechargeable Ni-Cd (nickel-cadmium)
Battery Voltage/ Recharging Time	DC 12 Volt / Approx. 30 minutes
Battery Charger (#BN-12VChgr)	110-240 VAC, 50/60Hz
Operating Humidity	90% or under
Operating Temperature	0 to 50 degrees C (32 to 122 degrees F)
Warranty Period	One Year Limited



STANDARD EQUIPMENT
with #32 wire guide installed



37% More Wire than One Tie of 16 gauge.

The *BN-TIER* delivers a strong double tie wrap of 18 gauge galvanized wire to securely hold the rebars. Two 18 ga. wires (.081") verses one 16 ga. wire (.051"). Each wire spool ties 120-200 rebars, depending on the rebar sizes. Wire spools are quickly & easily changed.

The wire spools, batteries, battery charger and most internal and external parts are interchangeable with the discontinued *U-Tier* Brand.

<i>BN-TIER</i>	1 unit
Wire spool	10 units
Battery charger	1 unit
12V Battery pack	2 units
Battery terminal cap	2 units
Diagonal Cutter	1 unit
Handle cap	1 unit
Screw	1 unit
Plastic inlay	1 unit
Shoulder Strap	1 unit
Instruction manual	1 copy