

## **Additional Information:**

### **B-292 Series Angle-Framed Mirror/Shelf Combination**

#### B-292 Series Standard Stock Sizes

Model No.	Width	*Height	
B-292 1824	18"	24"	(46 x 61cm)
B-292 1830	18"	30"	(46 x 76cm)
B-292 1836	18"	36"	(46 x 91cm)
B-292 2436	24"	36"	(61 x 91cm)

\*Height includes shelf.

#### Special-Order Custom Size Mirrors

- Maximum size of one-piece mirror: 144" x 72" (366 x 183cm).
- Maximum frame size available: 186" x 72" (472 x 183cm) with two pieces of glass in one-piece frame furnished with I section molding with polished stainless steel exposed finish covering seam where two pieces of glass butt together.
- Shelves longer than 120" (305cm) will be furnished as two pieces butted together.
- Custom size mirrors lock to wall hanger with two concealed theft resistant screws in bottom of frame.
- To specify special sizes, use Series Number followed by width and height in inches. Example: B-292 132 x 48 (335 x 122cm).

B-292 Series Special Order Reflective Surfaces. Resist breakage and provide a measure of safety from broken glass but differ in color and reflective quality from standard glass mirrors.

B-2926 Polished Stainless Steel (up to 72" x 24"; 183 x 61cm)

B-2928 Tempered Glass (up to 120" x 48"; 305 x 122cm)

B-2929 Laminated Glass (up to 96" x 48"; 245 x 122cm)

#### Notes

- To specify mirrors, use Series Number followed by width and height in inches.
- Width dimension must always be stated first following Series Number.
- Mirrors must be installed with width and height dimensions as ordered.
- Mirror back and wall hanger cannot be installed side ways to reverse width and height dimensions.

### Concealed Wall Hanger for Theft-Resistant Mounting

- Simplifies installation.
- Mirror is held flush to wall by integral brackets at top and bottom of mirror back.
- Locking device secures mirror to concealed wall hanger.
- Locking device may be unlocked and mirror removed from wall for reglazing
- Provide minimum 3/4" (19mm) clearance at top of mirror for mounting on wall hanger and 1" (25mm) clearance on each side.

