

# electronic dishwashers'

		SEMI-INTEGRATED			
		FULLY-INTEGRATED			
		LFA-013 SS LFA-013 IX	LFA-073 IT LFA-073 SS	LFA-65 IT LFA-65 SS	LFA-65 ITX
<b>GENERAL FEATURES</b>					
Electronic control		•	•	•	•
Place settings		12	12	12	12
Alternative wash		•	•	•	•
Perfect Drying			•		
Heat drying		•		•	•
ECO-Sensor			•		
Variable consumption		•	•	•	•
Can be connected to the hot water network		•	•	•	•
Third Sprinkler			•		
Third Sprayer		•		•	•
<b>WASH CYCLES</b>					
Pre-wash		•	•	•	•
Normal (150°F)		•		•	•
Intensive (155°F)		•	•	•	•
Heavy duty (161°F)		•	•	•	•
Economy (150°F)		•	•	•	•
Programs	Express 15 minutes (105°F)		•		
	Mixed (130°F)		•		•
	Quick (130°F)	•	•	•	•
	Automatic (130-150°F)		•		
	Total number of wash programs	6	8	6	6
	<b>CONTROLS</b>				
Dual Zone			•	•	•
Hygienizer		•			
Buttons	Time delay	3, 6, 9 h	Display (19 h)	3, 6, 9 h	3, 6, 9 h
	Start-Stop control	•	•	•	•
	Start-Pause control	•			
	Wash stage indicator	•			
Cycle pilot				•	•
Time remaining indicator			Display		
Rinse Aid indicator		•	•	•	•
Acoustic signal		•	•	•	•
<b>RACKS</b>					
Effortless telescoping upper rack		•	•	•	•
Bottom rack with folding supports		•	•	•	•
<b>SAFETY</b>					
Hidden element		•	•	•	•
Aqua-stop		•	•	•	•
Anti-overflow		•	•	•	•
Aqua-control		•	•	•	•
Anti-water return		•	•	•	•
Anti-Heating		•	•	•	•
<b>ENERGY CARD</b>					
Noise pressure		38	33	35	35
Noise power		50	45	47	47
<b>ELECTRICAL REQUIREMENTS (120V, 60Hz, 12A)</b>					
Total power (W)		1360	1360	1360	1360
Consumption/cycle: Water (gallons)		3.70	3.70	3.70	3.70
<b>DIMENSIONS</b>					
Height adjustment on feet (max. 23/4")		•	•	•	•
Front level adjustment		•	•	•	•
Dimensions without worktop (inches)	Height	32 1/4"	32 1/4"	32 1/4"	32 1/4"
	Width	23 7/16"	23 7/16"	23 7/16"	23 7/16"
	Depth	22 7/8"	21 1/2" / 22"	21 1/2" / 22"	22"