

*Complement  
your purchase  
with these  
fine accessories  
also from  
GINGER®:*

*Towel Bars  
Towel Rings  
Toilet Tissue Holders  
Hooks  
Soap Dishes  
Tumbler Holders  
Toiletry Shelves  
Grab Bars  
Mirrors  
Lights  
Bud Vases  
Hotel Shelves  
Shower Curtain Rods  
Soap & Bottle Baskets  
Cabinet Hardware*



460-N Greenway Industrial Drive  
Fort Mill, SC 29708

[www.gingerco.com](http://www.gingerco.com)

# KUBIC DOUBLE LIGHT

## INSTALLATION INSTRUCTIONS



# KUBIC LIGHT

MODEL 3682

ADA COMPLIANT



## INSTALLATION INSTRUCTIONS:

THESE LIGHTS SHOULD BE INSTALLED BY A LICENSED ELECTRICAL CONTRACTOR.

POWER REQUIREMENTS: 100-120 VOLTS

SAFETY: TO PREVENT ELECTRICAL SHOCK, BE SURE THAT THE POWER IS OFF BEFORE STARTING INSTALLATION.

### NOTES TO INSTALLER:

A. THE BACKPLATE OF THIS FIXTURE WILL COVER A HOLE WITH A MAXIMUM DIAMETER OF 3 3/8" (86 mm). THE CROSSBAR IS DESIGNED TO MOUNT DIRECTLY ONTO A 3" DIAMETER ROUND RAISED COVER PLATE (ALSO CALLED A ROUND PLASTER RING OR A ROUND RAISED MUD RING.) THE COVER PLATE SHOULD NOT PROTRUDE FROM THE FINISHED WALL SURFACE.

B. THIS LIGHT MAY BE INSTALLED INVERTED IF PREFERRED.

### INSTALLATION:

1. INSTALL CROSSBAR ONTO RAISED COVER PLATE.
2. CONNECT THE HOUSE GROUND WIRE TO THE CROSSBAR WITH THE ATTACHED GREEN GROUND SCREW.
3. FEED THE LIGHT FIXTURE WIRES THROUGH THE SPINDLE ON THE CROSSBAR.
4. CONNECT THE WHITE WIRES OF THE FIXTURE TO THE HOUSE NEUTRAL (WHITE) WIRE WITH A WIRENUT.
5. CONNECT THE BLACK WIRES OF THE FIXTURE TO THE HOUSE HOT (BLACK) WIRE WITH A WIRENUT.
6. SLIDE THE FIXTURE OVER THE SPINDLE OF THE CROSSBAR UNTIL THE BACKPLATE IS FLUSH AGAINST THE WALL. TIGHTEN THE SETSCREW WITH THE PROVIDED WRENCH.
7. INSTALL LIGHT BULBS.
8. SCREW SHADES ONTO THE FIXTURE. DO NOT OVERTIGHTEN.

