

ASSEMBLY INSTRUCTIONS

1. Before beginning the assembly, carefully unpack and identify all parts, referring to the illustration.
2. Position the BASE onto a flat work surface. Thread the top end of the CENTER TUBE onto the nipple on the bottom center of the CENTER COLUMN. Hand tighten until snug. Proceed to thread the end of the CENTER TUBE onto the nipple on the top center of the BASE. Tighten until snug. **Please make sure the holes on the bottom of the CENTER COLUMN line up the SCREWS on the BASE.**
3. Locate the SIDE RODS. Position the open end of the SIDE ROD through the hole on the bottom of the CENTER COLUMN. And then drop down the SIDE ROD and thread the nipple end onto the SCREWS on the BASE. Hand tighten until snug.
4. Thread the short nipple end of the CENTER STEM ASSEMBLY into the mounting hole on the top center of the JUNCTION BOX. Hand tighten until snug. Proceed to position the PLAIN WASHERS, RUBBER WASHERS, and the SHADE over the other end of the CENTER STEM ASSEMBLY as shown. Secure them together with the HEX NUT. Hand tighten until snug.
5. Locate the CAP over the top end of the CENTER STEM ASSEMBLY and secure with the FINIAL. Hand tighten until snug.
6. Install bulbs referring to the fixture markings and/or labels for maximum wattage.
7. Plug the SUPPLY WIRE into the OUTLET BOX. Retain this sheet for future reference.

