


# Product Specifications Report



Job Name:		Job Type:	
Comments:		Quantity:	
<b>1207: Manufactured by Sea Gull Lighting</b>		<b>Dimensions:</b>	
 <p><b>1207 - New Construction / Non-IC Recessed Lighting</b></p> <p>The low voltage MR-16 Mini-Recessed Lighting Non-IC Housing for new construction is UL listed for damp locations and near insulation. Its thermal protector safeguards against overheating. Other features include captive nails for fast installation, adjustable bar hangers, snap-on covers on junction box, and we provide integral magnetic transformer offering years of trouble-free operation. It accommodates up to 50w 12v MR-16 lamp.</p> <p><b>UPC #:</b> 785652120701      <b>Fixture Type:</b> Ambiance</p> <p><b>Finish:</b></p>		Length: 11"	
		Diameter: 4 1/4"	
		Width: 6 3/4"	
		Height: 5 1/2"	
		<b>Bulbs:</b>	
1 - GX5.3 Bi-Pin Halogen MR16 50w max 12v - Bulb Not Included		<b>Material List:</b>	
		Material #1: Housing - Steel - Raw Steel	
		<b>Safety Listing:</b>	
		cUL Listed for Dry Locations	

Light Bulb Data:											
Product #			Type	Base	Watts	Watts Consumed	Volts	Hours	Lumens	Temp (°K)	CRI
9709		Halogen	Halogen MR16	GU5.3	50	50	12v	2000	15? NSP 15?	3050	
9710		Halogen	Halogen MR16	GU5.3	50	50	12v	2000	25? NFL 25?	3050	
9711		Halogen	Halogen MR16	GU5.3	50	50	12v	2000	38? FL 40? (38?)	3050	

<b>Features:</b>	
Replacement Bulb(s) Order: 9709, 9710, 9711	
<b>Instruction Sheets</b>	
•English(HC-675) •French(n/a)	

Shipping Information (UPS Shipable: YES)														
Individual	Weight	Length	Width	Height	Carton	Weight	Length	Width	Height	Case	Weight	Length	Width	Height
Qty: 1	4.2 lbs	5.8"	6.8"	14.3"	Qty:6	28 lbs	15.4"	19.2"	9.4"	Qty:204	856.8 lbs	48"	40"	63.7"

Create PDF