

SPEAKMAN®

ANYSTREAM 2000®



S-2005



S-2005-HOTEL

Showerheads

S-2005

Polished chrome plated Anystream 2000 showerhead. Swivel ball connector. Spray adjusting T-handle. 3-1/4" face. 5 self cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzle delivers eight pulsating massage jets. Combination spray available. Integral volume and velocity control ring allows a full range of flow regulation for individual intensity preferences as well as water and energy conservation. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPSM inlet.

S-2005-HOTEL

Polished chrome plated Anystream 2000 showerhead. Swivel ball connector. Spray adjusting T-handle. 3-1/4" face. 5 self cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzle delivers eight pulsating massage jets. Combination spray available. Water conserving pressure compensating Autoflo device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPSM inlet.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> BB	Bright Brass Finish
<input type="checkbox"/> BP	Blister Pack Packaging (S-2005 only)
<input type="checkbox"/> WHT	White Finish

This space for Architect/Engineer approval.

Speakman Company

P.O. Box 191, Wilmington, DE 19899-0191 USA
1-800-537-2107 Fax: 1-800-977-2747

www.speakmancompany.com



SH5