

SPEAKMAN®

ANYSTREAM®



S-2252-1776



S-2253-AF

Showerheads

S-2252-1776

Limited Edition Liberty Bell showerhead. Brass ball swivel joint. Brass shank. Solid brass construction with polished chrome plated brass spray adjusting handle. 2-3/4" face. 6 Lexan® self-cleaning, deposit resisting plungers with 48 spray channels. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet. Includes individually numbered information card describing the history of the Liberty Bell.

S-2253-AF

Polished chrome plated Anystream showerhead. Brass ball swivel joint. Chrome plated shank. Spray adjusting T-handle. 2-1/2" face. 4 Lexan self-cleaning, deposit resisting plungers with 32 spray channels. Water conserving pressure compensating Autoflo device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet.

OPTIONS FOR S-2253-AF ONLY

SUFFIX	DESCRIPTION
<input type="checkbox"/> BB	Bright Brass Finish
<input type="checkbox"/> BP	Blister Pack Packaging
<input type="checkbox"/> WGTPCBP	White with Polished Chrome Trim

This space for Architect/Engineer approval.

Anystream and Autoflo —
Registered T.M. Speakman Company
Lexan — Registered T.M. General Electric
© Copyright, Speakman Company, 2005

Speakman Company

P.O. Box 191, Wilmington, DE 19899-0191 USA
1-800-537-2107 Fax: 1-800-977-2747
www.speakmancompany.com

SH3

