

ANYSTREAM®



SD-02



S-2252-AF

Showerheads

□ SD-02

Polished chrome plated Anystream showerhead. Brass ball swivel joint. Brass shank. Contoured polished chrome plated brass spray adjusting handle. 2-3/4" face. 6 Lexan® self-cleaning, deposit resisting plungers with 48 spray channels. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet.

□ S-2252-AF

Polished chrome plated Anystream showerhead. Brass ball swivel joint. Brass shank. Spray adjusting T-handle. 2-3/4" face. 6 Lexan self-cleaning, deposit resisting plungers with 48 spray channels. Water conserving pressure compensating Autoflo device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet.

OPTIONS

SUFFIX	DESCRIPTION
□ BP	Blister Pack Packaging
□ BPT	1/2" British Pipe Thread Inlet
□ VR	Vandal-Resistant (S-2252-AF only)

OPTIONS FOR SD-02 ONLY

SUFFIX	DESCRIPTION
□ BLK	Black Finish
□ ORB	Oil Rubbed Bronze Finish
□ PC-PVD	Chrome & Brass Finish
□ PC-WHT	White & Chrome Finish
□ PVD	Polished Brass Finish
□ SB	Brushed Brass Finish
□ SC	Brushed Chrome Finish
□ SN	Brushed Nickel Finish

SH2 This space for Architect/Engineer approval.

Speakman Company

P.O. Box 191, Wilmington, DE 19899-0191 USA
 1-800-537-2107 Fax: 1-800-977-2747
www.speakmancompany.com

