

## ADJUSTA-SPRAY® AND COSMOPOLITAN® Showerheads



**S-2220-AF**



**S-2270-AF**



**S-2271-AF**

**□ S-2220-AF**

Polished chrome plated Adjusta-Spray showerhead. Brass ball swivel joint. Chrome plated shank. Spray adjusting T-handle. 2-1/2" face. 40 spray slots at various angles for complete coverage. Water conserving pressure compensating Autflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet.

**□ S-2270-AF**

Polished chrome plated Cosmopolitan showerhead. Chrome plated brass ball joint. Chrome plated shank. 2" fully adjustable black spray face. Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet.

**□ S-2271-AF**

Polished chrome plated Cosmopolitan showerhead. Adjustable ball joint. Chrome plated shank. 2" fully adjustable black spray face. Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPSM inlet with sealing washer.

**OPTIONS**

SUFFIX	DESCRIPTION
<input type="checkbox"/> BP	Blister Pack Packaging
<input type="checkbox"/> BPT	1/2" British Pipe Thread Inlet (S-2220 only)

This space for Architect/Engineer approval.

---



---

**Speakman Company**

P.O. Box 191, Wilmington, DE 19899-0191 USA  
 1-800-537-2107 Fax: 1-800-977-2747  
[www.speakmancompany.com](http://www.speakmancompany.com)



**SH7**